



2/3" 2.8/50mm C		2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=50mm		
MAX. DIAMETER (RATIO)		F=1:2.8~16		
ELEMENT		9 GROUPS 10 ELEMENTS		
PICTURE SIZE		6.6x8.8mm	5.4x7.2mm	4.8x6.4mm
ANGLE	VER. ANGLE	7.6°	6.1°	5.5°
	HOR. ANGLE	10.1°	8.2°	7.3°
	DIA. ANGLE	12.6°	10.3°	9.2°
DISTORTION (TV)		-0.02%		
SHOOTING RANGE AT	VER.	14.3mm	11.8mm	10.5mm
MINIMUM FOCUS	HOR.	19.1mm	15.7mm	13.9mm
DISTANCE	DIA.	23.9mm	19.6mm	17.4mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		12.8mm in air		
FILTER SCREW SIZE		M30.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ø25.0mm		REAR ø12.5mm
MOUNT		C-MOUNT		
EXIT PUPIL		-83.8mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 200lp/mm CORNER 140lp/mm		
LENS COATING		WIDE BAND MULTI COATING		
WEIGHT		170g		

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	LR1015KW
		機種名	2/3" F2.8 f=50mm		
2021.11.18	フィルタ径追加	機種番	LM50JC10M 外觀図		
2014.12.25	更新				
2013.4.15	作成年月日				