



		1" 1.8/12mm C	1"	2/3"	1/1.8"
FOCAL LENGTH		f=12mm			
F-NUMBER		F=1.8-16			
PICTURE SIZE		9.6x12.8mm	6.6x8.8mm	5.4x7.2mm	
ANGLE OF VIEW (∞)	VER. ANGLE	44.5°	31.1°	25.5°	
	HOR. ANGLE	58.0°	41.0°	33.8°	
	DIA. ANGLE	70.1°	50.5°	41.9°	
DISTORTION (TV)		-1.6%	-0.97%	-0.69%	
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	175mm	119mm	97mm	
	HOR.	237mm	160mm	130mm	
	DIA.	300mm	202mm	164mm	
MINIMUM FOCUS DISTANCE		0.2m			
FLANGE BACK		17.526mm in air			
BACK FOCUS		11.1mm in air			
FILTER SCREW SIZE		M34x0.5			
FRONT/REAR EFFECTIVE DIA.		FRONT φ23.2mm		REAR φ14.7mm	
MOUNT		C-MOUNT			
EXIT PUPIL		-46.6mm			
TEMPERATURE RANGE		-10~+50°C			
STORAGE TEMPERATURE RANGE		-20~+60°C			
RESOLUTION CENTER/CORNER		CENTER 160lp/mm		CORNER 100lp/mm	
WEIGHT		175g			

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	LM12HC-VS
		機種名	1" f=12mm F1.8 VIS-SWIR		
		機種番	LM12HC-VIS-SW		
2020.09.15	作成年月日				S10-588