



1" 1.8/16mm C		1"	2/3"	1/1.8"
FOCAL LENGTH		f=16mm		
MAX. DIAMETER (RATIO)		F=1:1.8~16		
ELEMENT		9 GROUPS 11 ELEMENTS		
PICTURE SIZE		9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE	VER. ANGLE	33.6°	23.3°	19.2°
	HOR. ANGLE	44.0°	30.9°	25.5°
	DIA. ANGLE	53.7°	38.2°	31.6°
DISTORTION (TV)		0.02%		
SHOOTING RANGE AT	VER.	69.9mm	48.0mm	39.2mm
MINIMUM FOCUS	HOR.	93.5mm	64.0mm	52.3mm
DISTANCE	DIA.	117.1mm	80.2mm	65.5mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		13.0mm in air		
FILTER SCREW SIZE		M34x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT $\phi$ 27mm		REAR $\phi$ 16.5mm
MOUNT		C-MOUNT		
EXIT PUPIL		-38.0mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 160本/mm		CORNER 120本/mm
LENS COATING		WIDE BAND MULTI COATING		
WEIGHT		240g		

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	SC1101
2015.12.25	更新	機種名	1" F1.8 f=16mm		
2014.4.3	F値修正(16←22)				
2013.11.12	更新	機種番	LM16SC 外観図		
2013.4.15	作成年月日				