



|  |            |                 |                |         |
|--|------------|-----------------|----------------|---------|
| 2/3" 1.4/12mm C                                |            | 2/3"            | 1/1.8"         | 1/2"    |
| FOCAL LENGTH                                   |            | f=12mm          |                |         |
| MAX. DIAMETER (RATIO)                          |            | F=1:1.4~Close   |                |         |
| PICTURE SIZE                                   |            | 6.6x8.8mm       |                |         |
| ANGLE  | VER. ANGLE | 29.1°           | 24.0°          | 21.4°   |
|  | HOR. ANGLE | 38.3°           | 31.7°          | 28.3°   |
|  | DIA. ANGLE | 46.8°           | 39.4°          | 35.0°   |
| DISTORTION (TV)                                |            | -0.07%          |                |         |
| SHOOTING RANGE AT<br>MINIMUM FOCUS<br>DISTANCE | VER.       | 82.5mm          | 68.2mm         | 60.6mm  |
|  | HOR.       | 110.0mm         | 91.3mm         | 81.0mm  |
|  | DIA.       | 140.0mm         | 114.4mm        | 101.6mm |
| MINIMUM FOCUS DISTANCE                         |            | 0.15m           |                |         |
| FLANGE BACK                                    |            | 17.526mm in air |                |         |
| BACK FOCUS                                     |            | 11.7mm in air   |                |         |
| FILTER SCREW SIZE                              |            | M27x0.5         |                |         |
| FRONT/REAR EFFECTIVE DIA.                      |            | FRONT φ15.8mm   | REAR φ14.1mm   |         |
| MOUNT  |            | C-MOUNT         |                |         |
| EXIT PUPIL                                     |            | -225.0mm        |                |         |
| TEMPERATURE RANGE                              |            | -10~+50°C       |                |         |
| STORAGE TEMPERATURE RANGE                      |            | -20~+60°C       |                |         |
| RESOLUTION CENTER/CORNER                       |            | CENTER 100lp/mm | CORNER 80lp/mm |         |
| WEIGHT   |            | 85 g            |                |         |

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



|            |       |     |                  |      |         |
|------------|-------|-----|------------------|------|---------|
|            |       | 尺度  | 1/1              | 工場番号 | HR961KW |
|            |       | 機種名 | 2/3" F1.4 f=12mm |      |         |
| 2013.11.21 | 更新    | 機種番 | LM12JC1MS 外観図    |      |         |
| 2013.4.15  | 作成年月日 |     |                  |      |         |