



| 2/3" 1.4/16mm C | | 1/2" | 1/3" |
|---------------------------|------------|--|--------------|
| FOCAL LENGTH | | f=16mm | |
| MAX. DIAMETER (RATIO) | | F=1:1.4,4,8,16 | |
| ELEMENT | | 7群 8枚 | |
| PICTURE SIZE | | 6.6x8.8mm | 3.6x4.8 |
| ANGLE | VER. ANGLE | 22.7° | 12.3° |
| | HOR. ANGLE | 30.0° | 16.4° |
| | DIA. ANGLE | 37.0° | 20.4° |
| DISTORTION (TV) | | -0.05% | - |
| SHOOTING RANGE AT | VER. | 84.4mm | 45.9 |
| MINIMUM FOCUS | HOR. | 112.8mm | 61.2 |
| DISTANCE | DIA. | 141.2mm | 76.7 |
| MINIMUM FOCUS DISTANCE | | 0.2m | |
| FLANGE BACK | | 17.526 mm in air | |
| BACK FOCUS | | 13.1mm in air (Mechanical 13.1mm in air) | |
| FILTER SCREW SIZE | | M27x0.5 | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ20.2mm | REAR φ15.5mm |
| MOUNT | | C-MOUNT | |
| EXIT PUPIL | | 340mm | |
| TEMPERATURE RANGE | | -10~+50°C | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | |
| RESOLUTION CENTER/CORNER | | 中心100本/mm / 周辺 80本/mm | |
| WEIGHT | | g | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | |
|-----------|-------|----------------------|-------|-------|
| | | 尺度 1/1 | 承認 八木 | 製図 八木 |
| | | 機種名 2/3" F1.4 f=16mm | | |
| 2014.2.24 | 作成年月日 | LM16JCM-V | | |