

Ø23 2.0/50mm C						
FOCAL LENGTH		f=50mm				
MAX. DIAMETER (RATIO)		F=1:2.0~22				
ELEMENT		6 GROUPS 7 ELEMENTS				
PICTURE SIZE		13.8×18.4mm				
ANGLE VE	R. ANGLE	15.7°				
HO	R. ANGLE	20.6°				
DIA. ANGLE		25.4°				
DISTORTION (TV)		0.8%				
SHOOTIG RANGE AT	VER.	75mm				
MINIMUM FOCUS	HOR.	100mm				
DISTANCE	DIA.	124mm				
MINIMUM FOCUS DISTANCE		0.3m				
FLANGE BACK		17.526mm in air				
BACK FOCUS		21.6mm in air				
FILTER SCREW SIZE		M37.5×0.5				
FRONT/REAR EFFECTIVE DIA.		FRONT Ø31.8mm REAR Ø16.0mm				
MOUNT		C-MOUNT				
EXIT PUPIL		-19.1mm				
TEMPERATURE RANGE		-10~+50°C				
STORAGE TEMPERATURE RANGE		-20~+60°C				
RESOLUTION CENTER/CORNER		CENTER 160本/mm CORNER 80本/mm				
LENS COATING		WIDE BAND MULTI COATING				
WEIGHT		220 g				

NOTE:Specifications and availability are subject to change without notice注)本仕様については、予告なしに変更する場合があります。



		尺度	1/1	承 八木	製富永
		機種名	Ø23 F2.0 f=50mm		
2010.06.01	作成年月日	機種番	LM50XC		