

Ø23 2.0/12mm C						
FOCAL LENGTH	f=12mm					
MAX. DIAMETER (RATIO)	F=1:2.0~22					
ELEMENT	10 GROUPS 12 ELEMENTS					
PICTURE SIZE	13.8×18.4mm					
ANGLE VER. ANGLE	59.6°					
HOR. ANGLE	74.9°					
DIA. ANGLE	86.8°					
DISTORTION (TV)	0.59%					
SHOOTIG RANGE AT VER.	136 mm					
MINIMUM FOCUS HOR.	182 mm					
DISTANCE DIA.	225 mm					
MINIMUM FOCUS DISTANCE	0.1m					
FLANGE BACK	17.526mm in air					
BACK FOCUS	13.0mm in air					
FILTER SCREW SIZE	M55x0.75					
FRONT/REAR EFFECTIVE DIA.	FRONT Ø44.8mm REAR Ø16.0mm					
MOUNT	C-MOUNT					
EXIT PUPIL	-31.8mm					
TEMPERATURE RANGE	-10~+50°C					
STORAGE TEMPERATURE RANGE	-20~+60°C					
RESOLUTION CENTER/CORNER	CENTER 160本/mm CORNER 80本/mm					
LENS COATING	WIDE BAND MULTI COATING					
WEIGHT	270 g					

NOTE:Specifications and availability are subject to change without notice 注)本仕様については、予告なしに変更する場合があります。



		尺度	1/1	承 八木	製富永
		機種名	Ø23 F2.0 f=12mm		
2010.06.03	作成年月日	機種番	LM12XC		